

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY)

2. REPORT TYPE  
Technical Papers

3. DATES COVERED (From - To)

4. TITLE AND SUBTITLE

5a. CONTRACT NUMBER

5b. GRANT NUMBER

5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S)

5d. PROJECT NUMBER

2302

5e. TASK NUMBER

0378

5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)  
AFRL/PRS  
5 Pollux Drive  
Edwards AFB CA 93524-7048

8. PERFORMING ORGANIZATION  
REPORT

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Air Force Research Laboratory (AFMC)  
AFRL/PRS  
5 Pollux Drive  
Edwards AFB CA 93524-7048

10. SPONSOR/MONITOR'S  
ACRONYM(S)

11. SPONSOR/MONITOR'S  
NUMBER(S)

12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES

14. ABSTRACT

20030130 163

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:

17. LIMITATION  
OF ABSTRACT

18. NUMBER  
OF PAGES

19a. NAME OF RESPONSIBLE  
PERSON

Leilani Richardson

19b. TELEPHONE NUMBER  
(include area code)  
(661) 275-5015

a. REPORT

b. ABSTRACT

c. THIS PAGE

Unclassified

Unclassified

Unclassified

A

Standard Form 298 (Rev. 8-98)  
Prescribed by ANSI Std. Z39.18

4 different

papers enclosed for Task # 78

B Paper Rec'd After 30-day Deadline = 23 days until Deadline

MEMORANDUM FOR PRS (In-House Publication)

FROM: PROI (STINFO)

01 Nov 2002

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-AB-2002-260**  
C.T. Liu (PRSM) et al., "Investigating the Crack Growth Behavior in a Particulate Composite Material under Multi-Axial Loading Condition" (abstract only)

9<sup>th</sup> Int'l Conf. on the Mechanical Behavior of Materials  
(Geneva, Switzerland, 25-29 May 2003) (Deadline: 22 Nov 02)

(Statement A)

# **Investigating the Crack Growth Behavior in a Particulate Composite Material under Multi-Axial Loading Conditions**

C. T. Liu  
AFRL/PRSM  
10 E. Saturn Blvd.  
Edwards AFB CA 93524-7680, USA

M. Tam  
The Aerospace Co.  
El Segundo, CA 90250, USA

In past years, a considerable amount of work has been done studying crack growth behavior in particulate composite materials under different loading conditions at ambient pressure [1-4]. The basic approach used in characterizing the crack growth behavior in the particulate composite materials is based on linear elastic or linear viscoelastic fracture mechanics. Experimental findings indicate that power law relationships exist between the crack growth rate,  $da/dt$ , and the Mode I stress intensity factor,  $K_I$ . These experimental findings support the theory developed by Knauss [5] and Schapery [6] in their studies of crack growth behavior in linear viscoelastic materials. It is known that classical fracture mechanics principles, especially linear elastic fracture mechanics, are well established for single-phase materials. Experimental data indicate that linear fracture mechanics theories are applied to the particulate composite materials with varying degree of success. However, there has been relatively little effort in understanding the crack growth behavior in such materials under confining pressure condition.

In this study, pre-cracked specimens were used to study the crack growth behavior in a particulate composite material, containing hard particles embedded in a rubbery matrix, under constant strain conditions at 8697 KPa confining pressure. Three different applied strain levels, 12%, 15%, and 18%, were considered. In addition, the strain distributions near the crack tip were determined using imaging correlation techniques. The effects of strain levels on the crack growth behavior in the material were investigated and the results were discussed.

## **References**

- [1] Beckwith, S.W. and Wang, D.T., "Crack Propagation in Double-Base Propellants," AIAA Paper 78-170, 1978.

[2] Liu, C.T., "Crack Growth Behavior in a Composite Propellant with Strain Gradients – Part II," Journal of Spacecraft and Rockets, Vol. 27, (1990), pp. 647-659.

[3] Liu, C.T. "Crack Propagation in a Composite Solid Propellant," Proceedings of the Society of Experimental Mechanics, Spring Conference, (1990), pp. 614-620.

[4] Liu, C.T. and Smith, C.W., "Temperature and Rate Effects on Stable Crack Growth in a Particulate Composite Material," Experimental Mechanics, Vol. 36, No. 3 (1996), pp. 290-295.

[5] Knauss, W.G., "Delayed Failure – The Griffith Problem for Linearly Viscoelastic Materials," International Journal of Fracture Mechanics, Vol. 6, pp.7-20 March 1970.

[6] Schapery, R.A., On a Theory of Crack Growth in Viscoelastic Media, Report MM 2765-73-1, Texas A&M University, March 1973.